

### **Grange 05**

### Very Dark Grey Colour

| Total Solar Energy Rejected (TSER) | 67%  |
|------------------------------------|------|
| Visible Light Transmitted          | 5%   |
| Visible Light Reflected            | 10%  |
| Ultra Violet Rejected              | >98% |
| Glare Reduction                    | 95%  |
| Porous Sputtered                   | ✓    |
| Scratch Resistant Coating          | ✓    |
| Adhesive Type                      | HPR  |

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT





# **Grange 18**Dark Grey Colour

| Total Solar Energy Rejected (TSER) | 66%  |
|------------------------------------|------|
| Visible Light Transmitted          | 15%  |
| Visible Light Reflected            | 11%  |
| Ultra Violet Rejected              | >98% |
| Glare Reduction                    | 83%  |
| Porous Sputtered                   | ✓    |
| Scratch Resistant Coating          | ✓    |
| Adhesive Type                      | HPR  |

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT





# **Grange 28**Medium Dark Grey Colour

| Total Solar Energy Rejected (TSER) | 61%  |
|------------------------------------|------|
| Visible Light Transmitted          | 24%  |
| Visible Light Reflected            | 12%  |
| Ultra Violet Rejected              | >98% |
| Glare Reduction                    | 73%  |
| Porous Sputtered                   | ✓    |
| Scratch Resistant Coating          | ✓    |
| Adhesive Type                      | HPR  |

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT





# **Grange 38**Medium Grey Colour

| Total Solar Energy Rejected (TSER) | 58%  |
|------------------------------------|------|
| Visible Light Transmitted          | 24%  |
| Visible Light Reflected            | 12%  |
| Ultra Violet Rejected              | >98% |
| Glare Reduction                    | 60%  |
| Porous Sputtered                   | ✓    |
| Scratch Resistant Coating          | ✓    |
| Adhesive Type                      | HPR  |

<sup>\*</sup>Data derived from application to Pilkington automotive green glass 4mm with a 78% VLT

